

*TECHNICAL DATA SHEET*  
**TNT INSULATION FOIL**  
*FOR FLOATING FLOORS*



**Index**

Product details..... 1

## TNT INSULATION FOIL



Insulation suitable for direct installation under floating wood floors, laminates, carpet and rugs.

It increases the efficiency of heating thanks to the action of the reflective aluminum.

Thin: only 6 mm thick. Lightweight and easy to install.

Ideal in combination with the Heat Pak panels.



## TECHNICAL CHARACTERISTICS

ROLLS OF INSULATION FOR FLOATING FLOORS			
MODEL		AREA (m <sup>2</sup> ) / DIMENSIONS (m)	
h. 700	h.1000 mm	h. 700	h.1000 mm
TNT2.5-7	TNT2.5-10	2.5 / 0.7 X 3.6	2.5 / 1 X 2.5
TNT5.0-7	TNT5.0-10	5.0 / 0.7 X 7.25	5.0 / 1 X 5
TNT10-7	TNT10-10	10 / 0.7 X 14.5	10 / 1 X 10
TNT 25-7	TNT 25-10	25 / 0.7 X 35.7	25 / 1 X 25
TECHNICAL DATA			
THICKNESS		6 mm	
WEIGHT		0,85 Kg/m <sup>2</sup>	
VALUE R <sub>m</sub> (m <sup>2</sup> .K.W. <sup>-1</sup> )		0.19	
SOUND ABATMENT		25dB ΔLw IN CONJUNCTION WITH HEAT PAK	